



Keepower Battery Charger

Intelligent boat battery care

- The Keepower microprocessor ensures optimal charging.
- Keepower charges all battery types (AGM, GEL/WET, etc.)
- Keepower small & medium IP65 waterproof, large IP44
- Keepower can be constant connected - The battery will always be fully charged
- A built in battery indicator - enables you to decide whether to charge or not



Keepower charger series for boat batteries

Design: 30ART



Keepower SMALL 88813000

1A/12V or 4A/12V

The Keepower SMALL charger is the perfect all-round charger for the household. Suitable for motorcycles, lawn mowers, cars, boats, caravans and all other smaller electrical 12V vehicles. The keepower SMALL charger is IP65 protected and can be used outdoor in the rain.



Keepower MEDIUM 88813200

8A/12V

The Keepower MEDIUM charger is the perfect choice for household and semi professional user who needs a fast and powerful but yet simple charger for charging cars, boats and caravans. The keepower MEDIUM charger is equipped with a SUPPLY mode feature to avoid loss of the car's setup information, when changing batteries. The keepower MEDIUM charger is IP65 protected and can be used outdoor in the rain.



Keepower LARGE 88813400

15A/12V

The Keepower LARGE charger is the perfect choice for the professional workshop or garage user who needs an extremely powerful but yet simple charger for charging cars, trucks and caravans. Equipped with a very powerful SUPPLY Mode that ensures full battery even without the engine running. Capable of delivering 15A which makes it suitable for use in showrooms etc. and when servicing the car. The keepower LARGE charger is IP44 protected.



Keepower XLP 88813800

30A/15A 12V/24V

The Keepower XL-pro is the most power full professional charger in the Keepower lineup that combines 12 and 24V chargers in one intelligent unit. Comes with temperature sensor and possibility for charging your iPod, mobile and other electrical equipment via USB. Equipped with a very powerful SUPPLY Mode that ensures full battery even without the engine running. Capable of delivering 30A which makes it suitable for use in showrooms etc. And when servicing the car. The Keepower XL-pro charger is IP44



Nominal battery voltage	12V
Charge Current Ibatt	1A / 4A
Battery size	3Ah to 80Ah
Max. total outputpower	60W
Input voltage	230Vrms ± 10%
(Mains voltage)	50 Hz ± 3Hz
Ripple voltage	<100mVpp
(charging old battery with 40% capacity left)	
Current ripple	3%
(charging old battery with 40% capacity left)	
IP	65
Size of charger in mm	146*89*52
Charger cable size	0,75mm ² *1800mm
Lenght main cable	2800mm
Weight	0,490kg



Nominal battery voltage	12V
Charge Current Ibatt	8A
Battery size	20Ah to 160Ah
Max. total outputpower	120W
Input voltage	230Vrms ± 10%
(Mains voltage)	50 Hz ± 3Hz
Ripple voltage	<100mVpp
(charging old battery with 40% capacity left)	
Current ripple	3%
(charging old battery with 40% capacity left)	
IP	65
Size of charger in mm	200*118*70
Charger cable size	2,50mm ² *1800mm
Lenght main cable	2800mm
Weight	0,900kg



Nominal battery voltage	12V
Charge Current Ibatt	15A
Battery size	40Ah to 300Ah
Max. total outputpower	240W
Input voltage	230Vrms ± 10%
(Mains voltage)	50 Hz ± 3Hz
Ripple voltage	<100mVpp
(charging old battery with 40% capacity left)	
Current ripple	3%
(charging old battery with 40% capacity left)	
IP	44
Size of charger in mm	200*118*70
Charger cable size	02,55mm ² *1800mm
Lenght main cable	2800mm
Weight	0,900kg



Nominal battery voltage	12V/24V
Charge Current Ibatt	30A/15A
Battery size	3Ah to 600Ah
Max. total outputpower	525W
Input voltage	230Vrms ± 10%
(Mains voltage)	50 Hz ± 3Hz
Ripple voltage	<100mVpp
(charging old battery with 40% capacity left)	
Current ripple	3%
(charging old battery with 40% capacity left)	
IP	44
Size of charger in mm	200*118*70
Charger cable size	4mm ² *1800mm
Lenght main cable	2800mm
Weight	1,360kg